

FlexPoint™ FTTH UPS Power Series

FP1215, FP1232 & FP1250 Indoor 12VDC 15W, 32W & 50W UPS



FP1215 & FP1232 with 5 to 8Ah battery



FP1215, FP1232 & FP1250
with 12Ah battery

- Telecommunications grade power system provides 15W, 32W & 50W of 12VDC UPS power for FTTH applications
- Replaceable, 5Ah to 12Ah battery
- Battery management system provides optimum service life and runtime
- Local visual and audible status indicators and remote alarm interface
- Packet Cable™ interface options

Alpha extends its FlexPoint family with the addition of the FlexPoint FP1215, FP1232 & FP1250 telecommunications grade optical network terminal power supplies providing 15W, 32W or 50W of 12VDC primary and standby power for FTTH applications.

The FlexPoint 1215, 1232 & 1250 meet the telecommunications industry's most stringent requirements while providing aesthetically pleasing solutions for indoor residential installations. Both include onboard microprocessor based firmware engineered to achieve maximum battery life and system reliability.

Standby 12V power is provided by a 5 to 12Ah battery option, optimized by a battery management system. User interfaces include visual status indicators, audible alarm, a startup button and a multi-function silence button.

Input OPS	
AC Input Voltage:	110Vac or 240Vac
AC Input Frequency:	50/60Hz
Surge Protection:	Standard
	Level
	Telcordia GR-1089 ANSI/IEEE C62.41 IEC 61000-4-5
	1.2x50µs combination wave, 2kV

Output	FP1215	FP1232	FP1250
Operational Output Power (ONT Load):	15W max. continuous	32W max. continuous	50W max. continuous
Output Voltage:	12VDC nominal (battery voltage upon loss of AC)		

Mechanical	FP1215	FP1232	FP1250
Unit Dimensions for 5, 6.5, 7.2 or 8Ah Battery L x W x D (in/mm):	6.6x7.5x3.2/ 167.6x190.5x83.3	6.6x7.5x3.2/ 167.6x190.5x83.3	—
Unit Dimensions for 12Ah Battery L x W x D (in/mm):	—	6.6x7.5x4.3/ 167.6x190.5x109.3	6.6x7.5x4.3/ 167.6x190.5x109.3
Weight Without Battery (lb/kg):	1.2 / 0.54	1.3 / 0.58	1.4 / 0.63
5.0Ah Battery Weight (lb/kg):	3.9 / 1.8		
7.2Ah Battery Weight (lb/kg):	5.7 / 2.6		
8.0Ah Battery Weight (lb/kg):	5.73 / 2.7		
12Ah Battery Weight (lb/kg):	8.4 / 3.8		

Estimated Battery Runtimes	FP1215		FP1232		FP1250	
	7.5W Load	15W Load	16W Load	32W Load	36W Load	50W Load
5.1Ah Battery (hrs):	6.3	2.8	2.5	1.1	0.9	0.7
7.2Ah Battery (hrs):	9.9	4.2	3.9	1.6	1.4	1.0
8.0Ah Battery (hrs):	11.2	5.0	4.7	2.0	1.7	1.1
12Ah Battery (hrs):	17.3	8.0	7.5	3.3	2.9	2.0
Battery Type:	Maintenance free, leak-proof, sealed valve regulated lead acid (VRLA)					

Visual Indicators	
AC Power:	Green LED On: AC power present and powering the ONT
Battery:	Green LED On: Battery powering ONT during AC loss Green Flashing: Battery powering ONT during AC loss and running low
Replace Battery:	Red LED Off: Battery present and working correctly Red LED On: Replace battery / battery missing
Muted Indicator:	Green LED Light: Audible alarm is muted

Audible Status Indicators	
Loss of Input Power:	Single, one second chirp
Low Battery:	Single chirp every 15 seconds at 25% SOC
Replace Battery:	Double chirp spaced fifteen minutes apart

Push Buttons	
DC Start:	Press and hold when unit is off to start up on battery when AC is not present
Silence Alarm:	When any audible alarm is on, press this key at least 1 second and release to silence the audible alarm until power is cycled


Agency Compliance	
System:	FCC part 15 Class B, NRTL/C (60950-1), CE, C-Tick/RCM, RoHS to EU 2011_65_EC

Environment	
Storage Temperature:	-20 to 45°C / 4 to 113°F
Operating Temperature:	-20 to 45°C / 4 to 113°F
Humidity:	5 to 95% non condensing
Elevation Operation Maximum:	3,000m / 10,000ft derate at 2°C / 35.6°F per 304.8m / 1,000ft above 1,828.8m / 6,000ft
Elevation Storage Maximum:	15,000m / 50,000ft

Interface	
DC Output:	Removable screw terminal plug accepts (2) 16AWG and (5) 24AWG wires
AC Input:	IEC 320/C6 inlet
Line Cord:	NEMA 5-15 to IEC 320 C5 (other power cords available upon request)

Models and Power Line Cords			
FP1215	FP1232	FP1250	Power Line Cord (Determined by Model)
FP-1215-5A	FP-1232-8A	FP-1250-12A	120VAC 3-conductor NEMA 5-15 power cord
FP-1215-5B	FP-1232-8B	FP-1250-12B	230VAC 3-conductor Schuko input power cord
FP-1215-5C	FP-1232-8C	FP-1250-12C	230VAC 3-conductor United Kingdom input power cord
FP-1215-5D	FP-1232-8D	FP-1250-12D	240VAC 3-conductor Australia/New Zealand input power cord
—	FP-1232-8-6C	FP-1250-12-6C	120VAC 3-conductor NEMA 5-15 power cord with BC cable

Supporting Options	
AX-STDBAT-5:	Battery 5.1Ah AGM, 1 year warranty
AX-STDBAT-7:	Battery 7.2Ah AGM, 1 year warranty
AX-LONGBAT-7:	Battery 7.2Ah AGM, 3 year warranty
AX-LONGBAT-8:	Battery 8.0Ah AGM, 3 year warranty
AX-STDBAT-12:	Battery 12Ah AGM, 1 year warranty
FTTH-CBL:	ONT hook-up cable, 2x16AWG and 5x24AWG, CMX UL listed
12Ah Cover:	12Ah battery cover and velcro strap



Rear View
Mounting hole pattern options



Output Cable Connection



Worldwide Corporate Offices

North America Tel: +1 360.647.2360 Fax: +1 360.671.4936	Europe Tel: +49 9122.79889.0 Fax: +49 9122.79889.21
---	---

Latin America Tel: +561 792.9651 Fax: +561 792.7157	Asia Pacific Tel: +852 2736.8663 Fax: +852 2199.7988
---	--