



## INNBOX G92

High-end GPON FTTH Home Gateway and Mesh Wi-Fi Manager

**ISKRATEL**  
S&T Group



Full gigabit throughput



Top-of-the-line wireless performance



Unparalleled reach and coverage

**Wi-Fi 6**

**Innbox G92** home gateway delivers fibre connectivity over a GPON uplink, unlocking the true potential of gigabit connectivity by providing **multi-gigabit wireless** in even the biggest homes. This state-of-the-art home gateway guarantees uncompromised user experience with advanced triple-play services and multiple **ultra-high-definition TV** streams, delivered over wired or wireless home network.

Innbox G92 supports a smooth delivery of services such as internet and video – including multiple UHD TV streams – over **four gigabit Ethernet ports** or over **Wi-Fi 6 802.11ax** access point that operates at **2.4 GHz and 5 GHz** concurrently.

Furthermore, Innbox G92 embeds a management point for a gigabit mesh Wi-Fi network that ends the

headaches caused by dead zones. Complemented by Innbox satellite access points, the mesh Wi-Fi network ensures **seamless roaming and smooth handover**, never compromising the supreme user experience.

Adding to connectivity, Innbox G92 offers SIP-compatible VoIP services over FXS ports. One USB host port is

available for **value-added features**, such as a printer server, a file server, or an **LTE modem** for backup uplink connectivity.

The devices' embedded firewall, NAT and IP sharing deliver **secure internet access** to all connected users.

### KEY FEATURES AND BENEFITS

- Fully ITU G.984 GPON compliant with extended functionalities
- Powerful full-gigabit home-gateway with line-rate routing for advanced services and multiple UHD TV IP streams
- Multiple LAN interfaces: Gigabit Ethernet, Wi-Fi 6, Wi-Fi 5, concurrent 2.4 GHz/5 GHz, USB 2.0, FXS POTS
- Mesh Wi-Fi management
- Smooth multi-streaming and gaming with MU-MIMO
- Internal or external antennas
- Integrated fibre-termination unit



### WAN specifications

- Full compliance with ITU-T G.984.5 GPON, Class B+
  - SC/APC connector
  - DFB transmitter, 1310 nm, 1.25 Gbps upstream, launch power 0.5..5 dBm
  - APD receiver, 1490 nm, 2.5 Gbps downstream, input power overload –8 dBm; sensitivity –28 dBm
- Fully ITU-T G.984 compliant framing
- Multiple T-CONTs and GEM ports, multicast GEM port
- Activation with auto-discovery of SN and password in conformance with ITU-T
- AES-128 decryption with key generation and switching
- Forward error correction
  - 802.1p mapper service profile on U/S

### LAN interfaces

- Four ports Gigabit Ethernet 10/100/1000Base-TX (RJ-45)
  - Automatic MDI/MDIX crossover, Auto-negotiation and speed auto-sensing, half/full duplex support
  - Compliance with IEEE 802.3
- Two ports FXS (RJ-11) for POTS connection
- One port USB 2.0 with host connector

### Wireless LAN

- Wi-Fi access point 802.11b/g/n/ac/ax 2x2 and 2x2 MU-MIMO with internal or external antennas
- Simultaneous dual-band 2.4 GHz and 5 GHz
- Wi-Fi protected setup (WPS)
- WPA/WPA2/WPA3 in PSK mode or using EAP with RADIUS
- Access control list based on MAC address

### Mesh Wi-Fi

- Embedded management of mesh Wi-Fi satellite APs
- 802.11k/v compliant roaming and band steering

### Bridging

- Ethernet bridging/switching per IEEE 802.1D/802.1Q
- Traffic management (priority queuing, traffic shaping)
- QoS with support for IEEE 802.1p and DSCP
- Per-port IEEE 802.1Q VLAN ID processing
- VLAN tagging/untagging
- IGMP v2/v3 snooping
- Automatic MAC learning and aging
- Unlimited MAC addresses for OMCI-configured flows
- Support for 4096 MAC addresses for RG traffic flows
- Broadcast storm control

### IP routing

- IP routing: RIP1, RIP2, static routing
- RFC2684 (RFC1483) routed
- PPPoE client, PPPoE pass-through
- DHCP client, server and relay (RFC2131)
- (D)DNS client and relay
- IP multicast IGMP proxy
- RTP proxy PPPoE
- NAT/NAPT with port forwarding

### USB 2.0 applications

- File server (using USB disk, flash or HDD), DLNA
- Printer server
- 3G/LTE modem (optional)

### Security and QoS

- NAT (RFC3022) basic firewall with extensive ALG support
- Firewall with well-known applications setup
- URL filtering
- Time scheduler (parental control)
- DMZ/IP pass-through
- VPN pass-through
- ToS/DSCP-to-CoS mapping
- Bandwidth reservation
- Voice traffic prioritisation

### Configuration and network management

- OMCI
- UPnP/DLNA
- Simple port configuration
- Telnet for local or remote management
- Web for firmware upgrade and configuration
- Web-based management (multi-level GUI)
- TR-069 data-frame model, TR-098, TR-104, TR-106
- TR-143 testing and troubleshooting tools
- IPERF and TCP dump (optional)
- Buttons: WLAN, WPS, reset

### Voice support

- G.711 (64 kbps, A-law,  $\mu$ -law), G.729ab (8 kbps) (optional)
- Line echo cancellation G.168 with configurable tail
- Voice-activity detection, Comfort noise generation
- Adaptive jitter buffer and packet-loss compensation
- DTMF dialling, modem/fax tone detection and pass-through
- SIPv2 (RFC 3261), RTP (RFC3550)
- RTP profile for audio and video conferences (RFC 3551)
- RTP payload for DTMF events (RFC2833)
- Caller ID (Type-1 and 2)
- T.38 Fax

### Power

- External 115-230 V AC, 50-60 Hz, 12 V DC 1.5A

### Physical dimensions

- 226 mm x 140 mm x 48 mm

### Environment

- Operating: 0..40 °C, RH 20..90% non-condensing, compliant with ETSI 300 019-1-3, Class 3.1

### Certification

- CE, CB, RoHS compliant

Some features are hardware-dependent.

Some features might not be included in dedicated software releases.

Date of issue: 23 November 2021 / Version 4.0



**ISKRATEL**  
S&T Group

Iskratel, d. o. o., Kranj  
Ljubljanska cesta 24 a  
SI 4000 Kranj, Slovenia

P +386 4 207 20 00  
F +386 4 207 27 12

info@iskratel.si  
www.innbox.net  
www.iskratel.com



Telco



Transport



Energy



Public Safety